

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Natural Oil Woodstain Effect

Article number: 1140 Agate-Silver, 1142 Graphit-Silver, 1143 Onyx-Silver

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint
Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf
Germany

Further information obtainable from:

Product safety department
Tel.: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Additional information: For the wording of the listed hazard phrases refer to section 16.

2.2 Label elements

Hazard pictograms



GHS02

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat. - No smoking.
P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 1)

Additional information:

P273 Avoid release to the environment.
 P501 Dispose of contents/container in accordance with national regulations.
 EUH208 Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

2.3 Other hazards

EUH210 Safety data sheet available on request.
 Contains biocidal products: 3-Iodo-2-propynylbutylcarbamate
 Always wear a dust mask when sanding.
 Observe the general safety regulations when handling chemicals.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-48-9 EC number: 918-481-9	aliphatic hydrocarbons, C10-C13 ⚠ Asp. Tox. 1, H304, EUH066	20-40%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	5-15%
CAS: 127519-17-9 ELINCS: 407-000-3 Index number: 607-281-00-4	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl] propionates ⚠ Aquatic Chronic 2, H411	<3%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1	aluminium powder (stabilised) ⚠ Flam. Sol. 1, H228	1-≤2.5%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-Iodo-2-propynylbutylcarbamate ⚠ Acute Tox. 2, H330; ⚠ STOT RE 1, H372; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.1-<0.25%

SVHC Not applicable.

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.
 Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.
 In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 2)

After skin contact: Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact: If skin irritation or rash occurs: Get medical advice/attention.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Induce vomiting only, if affected person is fully conscious.
If swallowed, seek medical advice immediately and show this container or label.
Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
Carbon monoxide (CO)
carbon dioxide (CO₂)

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
General measures for chemical fires.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 3)

For non-emergency personnel

 Keep away from ignition sources.
 Wear protective clothing.

For emergency responders

No action shall be taken involving any personal risk or without suitable training.

6.2 Environmental precautions:

Wear protective equipment. Keep unprotected persons away.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for
containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose of the material collected according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

 Use only in well ventilated areas.
 Keep away from heat and direct sunlight.
 Keep receptacles tightly sealed.
 Prevent formation of aerosols.
 Open and handle receptacle with care.
 Avoid contact with skin and eyes.

General protective and hygienic measures:

 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.

Information about fire - and explosion protection:

 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 4)

Handling: Even a small sip can lead to life-threatening damage to the lungs. Keep rags filled with this liquid out of the reach of children.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by**

storerooms and receptacles: Store only in the original receptacle.
Store in a cool location.

Information about storage in

one common storage facility: Not required.

Further information about

storage conditions: Store receptacle in a well ventilated area.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

Storage class: TRGS 510 Storage class 3: Flammable liquids

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA	Short-term value: 1200 mg/m ³ CEFIC-HSPA
-----	--

34590-94-8 Dipropylene glycol monomethyl ether

IOELV	Long-term value: 308 mg/m ³ , 50 ppm Skin
-------	---

DNELs**34590-94-8 Dipropylene glycol monomethyl ether**

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	36 mg/kgKG/Tag
Dermal	DNEL Verbraucher (Langzeit - systemische Effekte)	121 mg/cm ²
Inhalative	Worker (chronic - Systemic health effec)	308 mg/m ³
	DNEL Verbraucher (Lanzzeit - systemische Effekte)	37.2 mg/m ³

7429-90-5 aluminium powder (stabilised)

Oral	DNEL Verbraucher (Langzeit - systemische Effekte)	3.95 mg/kgKG/Tag
Inhalative	Worker (chronic - Systemic health effec)	3.72 mg/m ³
	DNEL Arbeitnehmer (Langzeit - lokale Effekte)	3.72 mg/m ³

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 5)

PNECs	
34590-94-8 Dipropylene glycol monomethyl ether	
PNEC sea water	1.9 mg/l
PNEC fresh water	19 mg/l
PNEC sediment (fresh water)	70.2 mg/kg
PNEC sediment (sea water)	7.02 mg/kg
PNEC soil	2.74 mg/kg
PNEC sewage treatment plant interrupted release	4,168 mg/l 190 mg/l
7429-90-5 aluminium powder (stabilised)	
PNEC fresh water	0.0749 mg/l
PNEC sewage treatment plant	20 mg/l

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

Ensure good ventilation/exhaustion at the workplace.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.
 Immediately remove all soiled and contaminated clothing
 Do not inhale gases / fumes / aerosols.
 The usual precautionary measures are to be adhered to when handling chemicals.
 Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.
 See Section 7 for information on safe handling.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.
 Not necessary if room is well-ventilated.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387.
 Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection

Protective gloves
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 6)

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR
 Recommended thickness of the material: ≥ 0.4 mm
 For the mixture the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye/face protection

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Fluid

Colour:

According to product specification

Odour:

Mild

Odour threshold:

Not determined.

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

> 180 °C

Flammability

Flammable.

Lower and upper explosion limit**Lower:**

0.6 Vol %

Upper:

7.0 Vol %

Flash point:

43-59 °C (DIN EN ISO 2719)

Auto-ignition temperature:

240 °C

Decomposition temperature:

Not determined.

pH

Mixture is non-polar/aprotic.

Viscosity:**Kinematic viscosity at 20 °C**

43-60 s (DIN EN ISO 2431/4mm)

>21 mm²/s (40°C) (calculated)**Dynamic:**

Not determined.

(Contd. on page 8)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 7)

Solubility**water:**

Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.**Vapour pressure:** Not determined.**Density and/or relative density****Density at 20 °C:** 0.97-1.0 g/cm³ (DIN 51757)**Relative density** Not determined.**9.2 Other information****Appearance:****Form:** Fluid**Important information on protection of health and environment, and on safety.****Ignition temperature:** Product is not selfigniting.**Explosive properties:** Not determined.**Solvent content:****VOC (EC)** < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)**Change in condition****Evaporation rate** Not determined.**Information with regard to physical hazard classes****Explosives** Void**Flammable gases** Void**Aerosols** Void**Oxidising gases** Void**Gases under pressure** Void**Flammable liquids** Flammable liquid and vapour.**Flammable solids** Void**Self-reactive substances and mixtures** Void**Pyrophoric liquids** Void**Pyrophoric solids** Void**Self-heating substances and mixtures** Void**Substances and mixtures, which emit flammable gases in contact with water** Void**Oxidising liquids** Void**Oxidising solids** Void**Organic peroxides** Void**Corrosive to metals** Void**Desensitised explosives** Void**SECTION 10: Stability and reactivity****10.1 Reactivity**

No further relevant information available.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 8)

10.2 Chemical stability**Thermal decomposition /****conditions to be avoided:**

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

Reacts with acids, alkalis and oxidising agents.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous**decomposition products:**

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity**

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Inhalative	LC50 / 4h	33.2–<50.7 mg/l
------------	-----------	-----------------

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>19,020 mg/kg (rat)
		13,000–14,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,667 mg/l (rat)
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50 / 4h	0.67 mg/l (rat) (OECD 403 Acute Inhalation Toxicity)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin**sensitisation**

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 9)

Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
Subacute to chronic toxicity:	Based on available data, the classification criteria are not met.
Additional toxicological information:	The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.
Sensitisation	Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

11.2 Information on other hazards
Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity:
64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h	>1,000 mg/l (Daphnia magna)
IC50 / 72h	>1,000 mg/l (algae)
LC50 / 96h	>1,000 mg/l (fish)

34590-94-8 Dipropylene glycol monomethyl ether

EC50 / 48h	70.2 mg/l 1,919 mg/l (Daphnia magna)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

127519-17-9 A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates

EC50 / 48h	3.2 mg/l (Daphnia magna) (24h EC 50 acute immobilisation test)
Bioconceived factor	<3 (Flow-through fish test)

55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50 / 48h	0.16 mg/l (Daphnia magna)
EC50/ 72h	0.022 mg/l (algae)

12.2 Persistence and
degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 10)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment
PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects
Remark: Harmful to aquatic life with long lasting effects.
Harmful to fish

Behaviour in sewage processing plants:
55406-53-6 3-Iodo-2-propynylbutylcarbamate

EC50/ 96h | 0.067 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

Additional ecological information:
General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 Disposal must be made according to official regulations.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents:

 Solvent naphtha
 Osmo Brush Cleaner and Thinner

SECTION 14: Transport information

14.1 UN number or ID number
ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name
ADR

1263 PAINT

(Contd. on page 12)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 11)

IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
	
Class	3 (F1) Flammable liquids.
Label	3
<hr/>	
IMDG, IATA	
	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	
Hazard identification number (Kemler code):	Warning: Flammable liquids. 30
EMS Number:	F-E,S-E
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	
	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
<hr/>	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 12)

UN "Model Regulation":

UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2004/42/EC

Product type: PAINTS AND VARNISHES

- Product subcategory: Interior/exterior trim varnishes and woodstains, including opaque woodstains

- Solvent-borne coatings, Limit value: 400 g/l

VOC: <400 g/l

Directive 2012/18/EU

Named dangerous

substances - ANNEX I

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes)

for the application of lower-

tier requirements

5,000 t

Qualifying quantity (tonnes)

for the application of upper-

tier requirements

50,000 t

REGULATION (EC) No

1907/2006 ANNEX XVII

Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Marking in accordance with biocide guideline 98/8/EG

55406-53-6 | 3-Iodo-2-propynylbutylcarbamate

1 g/kg

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 13)

VOC (EC) < 400 g/l (VOC-max. Cat A/e (2010) = 400 g/l)

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases	H228 Flammable solid.
	H302 Harmful if swallowed.
	H304 May be fatal if swallowed and enters airways.
	H317 May cause an allergic skin reaction.
	H318 Causes serious eye damage.
	H330 Fatal if inhaled.
	H372 Causes damage to organs through prolonged or repeated exposure.
	H400 Very toxic to aquatic life.
	H410 Very toxic to aquatic life with long lasting effects.
	H411 Toxic to aquatic life with long lasting effects.
	EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to
Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Date of previous version: 25.10.2021

Version number of previous version: 8.2

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Sol. 1: Flammable solids – Category 1
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 2: Acute toxicity – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.12.2023

Version number 9.0 (replaces version 8.2)

Revision: 13.12.2023

Trade name: Natural Oil Woodstain Effect

(Contd. of page 14)

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

ECHA Portal

Safety data sheets from raw material suppliers

ESIS : European chemical Substances Information System

*** Data compared to the
previous version altered.**